



Specification_ Side Discharge Universal Series - Cooling Only

Outdoor Unit			EKOUT-18	EKOUT-24	EKOUT-30	EKOUT-36	EKOUT-36	EKOUT-42	EKOUT-48	EKOUT-60
Capacity	Cooling Capacity	Btu/h	18000	24000	30000	36000	36000	42000	48000	60000
		kW	5.3	7.1	9.0	10.5	10.5	12.0	14.0	16.0
	Heating Capacity	Btu/h	---	---	---	---	---	---	---	---
		kW	---	---	---	---	---	---	---	---
Performance	Power Supply	V~, Hz, Ph	220-240, 50, 1	220-240, 50, 1	220-240, 50, 1	220-240, 50, 1	380-420, 50, 3	380-420, 50, 3	380-420, 50, 3	380-420, 50, 3
	Air Flow Volume(m ³ /h)		3400	3400	4800	4800	4800	5800	6000	6050
	Noise Level(dB(A))		56	56	58	58	58	60	58	58
Dimension & Weight	Net Dimension (mm)	WxHxD	842x695x324	842x695x324	895x862x313	895x862x313	895x862x313	990x966x354	900x1167x340	900x1167x340
	Net Weight(kg)		42	49	62	84	79	97	99	103
	Packing Dimension (mm)	WxHxD	965x755x395	965x755x395	1043x915x395	1043x915x395	1043x915x395	1120x1100x435	1032x1307x443	1032x1307x443
	Gross Weight(kg)		45	51	67	89	84	101	103	107
Piping Size	Liquid Size(mm)		Ø6.4	Ø9.5	Ø9.5	Ø9.5	Ø9.5	Ø9.5	Ø9.5	Ø9.5
	Gas Size(mm)		Ø12.7	Ø15.9	Ø15.9	Ø19.0	Ø19.0	Ø19.0	Ø19.0	Ø19.0
	Max. pipe length(m)		25	25	30	30	30	50	50	50
	Max. height difference(m)		15	15	15	20	20	25	25	25
Stuffing Quantity	20'/40'/40'HQ	Unit	100/208/216	100/208/216	50/106/108	50/106/108	50/106/108	27/55/56	27/55/56	27/55/56