



## Specification\_ Top Discharge Universal Series\_Cooling only

		Outdoor Unit	EKOVT-18	EKOVT-24	EKOVT36	EKOVT-48	MOVT-60
Capacity	Cooling Capacity	Btu/h	18000	24000	36000	48000	60000
		kW	5.3	7.1	10.5	14.0	16.0
	Heating Capacity	Btu/h	—	—	—	—	—
		kW	—	—	—	—	—
Performance	Power Supply	V~, Hz, Ph	220-240, 50, 1	220-240, 50, 1	220-240, 50, 1	380, 50, 3	380-415, 50, 3
	Air Flow Volume(m <sup>3</sup> /h)		4500	4500	6400	6400	6400
	Noise Level(dB(A))		58	60	60	60	60
Dimension & Weight	Net Dimension (mm)	WxHxD	554x636x554	554x636x554	740x852x740	740x852x740	740x852x740
	Net Weight(kg)		50	54	90	90	94
	Packing Dimension (mm)	WxHxD	580x700x580	580x700x580	770x890x770	770x890x770	770x890x770
	Gross Weight(kg)		53	57	95	95	99
Piping Size	Liquid Size(mm)		Ø6.4	Ø9.5	Ø12.7	Ø12.7	Ø12.7
	Gas Size(mm)		Ø12.7	Ø15.9	Ø19.0	Ø19.0	Ø19.0
	Max. pipe length(m)		25	25	30	50	50
	Max. height difference(m)		15	15	20	25	25
Stuffing Quantity	20'/40'/40'HQ	Unit	120/240/240	120/240/240	42/90/133	42/90/133	42/90/133